

IP54

Series
OL500



**Wide Range of Oil Viscosity. Cost-Efficient.
Refillable.**



Pulsarlube **OL500**

Pulsarlube OL500

High Cost-Efficient
Economical Oil Lubricator



Features&Advantages

Outstanding Features

- ▶ A vertical feed pump controlled by a microprocessor allows a wide oil viscosity range
- ▶ Large 500ml oil reservoir and battery pack

Cost Savings

- ▶ Lower maintenance costs than manual lubrication
- ▶ Refillable oil reservoir and battery pack

Single Point Lubrication

High output pressure (10kgf/cm²)

User Friendly Programming

Easy to program with built-in LCD and simple button controls

Easy Maintenance

Transparent container for easy visual inspection of remaining oil

Others

- ▶ Various dispensing settings to suit all industrial applications
- ▶ Auto Lockout mode to prevent unintentional system changes
- ▶ Easy to install in hazardous & confined areas



Typical Applications



— Bearings

— Chains

— Cable Ropes

— Cable Tracks

— Pumps

— Motors

— Escalators, etc.



Details



Specifications

Oil Volume Capacity

500ml (refillable)

Operating Pressure

10kgf/cm² (depends on oil viscosity)

Operating Temperature

-15°C ~ 60°C (5°F ~ 140°F) w/
Standard Alkaline Battery

Power Supply

DC 4.5V Battery Pack (replaceable)

Oil Viscosity Range

10~10,000 cSt@40°C

Dispensing Periods

1, 2, 4, 6, 12, 18, 24 month & H (15 days)

Product Certifications & IP Code

IP54

Remote Installation

Max. 6m (20ft) with Ø4 tube
(up to 4 lube points)