

1. Product Description (Benefits)

- ✓ Maximum protection from rust and corrosion
- ✓ Good anti-wear and high speed and load carrying capacity (Mo type)
- ✓ Quality proved item, which has used over 10 years in leading automatic lubricator maker
- ✓ Wide service temperature (-30 °C ~ 130 °C)
- ✓ Mineral oil + Lithium complex, Yellowish brown

2. Application Part

- ✓ Constant velocity joints for automobiles
- ✓ Automatic grease lubricator
- ✓ Anti-wear, Anti-rust, high speed and load-carrying capacity

3. Product Data

Test item	Test method	Result
Copper Corrosion grade	ASTM D 4048	1A
Worked Penetration 0.1mm	ASTM D 217	305 ~ 310
Dropping Point °C	ASTM D 566	190
Oil Separation wt%	KS M 2050	2.0
Evaporation Loss wt%	ASTM D 972	0.4
Worked Stability 0.1mm	KS M 217	350
Extreme-Pressure Properties N	ASTM D 2596	400

Note : The above data constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field test with the product selected for a specific application

4. Suggestion of Using

- ✓ Grease gun, various spreading apparatus, brush and automatic lubricating system

※ Storage : Approx. 12 months if the product is stored in the original closed container in a dry place