

### 1. Product Description (Benefits)

- ✓ Excellent pump ability in central lubrication systems
- ✓ Good resistance to ambient media, water and water steam
- ✓ Good anti-wear and load carrying capacity, corrosion protection
- ✓ Good sealing effect, good adhesion
- ✓ Wide service temperature (-15 °C ~ 160 °C)
- ✓ Mineral oil + Urea, Beige

### 2. Application Part

- ✓ Drive rollers, Conveyor rollers
- ✓ Automatic grease lubricator
- ✓ Heating furnaces, drying stove
- ✓ Opening gate of bulk material equipment, Cooling bed conveyor system

### 3. Product Data

Test item	Test method	Result
<b>Copper Corrosion grade</b>	ASTM D 4048	1A
<b>Worked Penetration 0.1mm</b>	ASTM D 217	320
<b>Dropping Point °C</b>	ASTM D 566	> 260
<b>Oil Separation wt%</b>	KS M 2050	1.2
<b>Water washout characteristic wt%</b>	ASTM D 1264	1
<b>Evaporation Loss wt%</b>	ASTM D 972	0.12
<b>Extreme-Pressure Properties N</b>	ASTM D 2596	> 250

Note : The above data constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field test with the product selected for a specific application

### 4. Suggestion of Using

- ✓ General automatic lubricating system and lubrication supply system
- ✗ Storage : Approx. 12 months if the product is stored in the original closed container in a dry place